Regular use

Disposable

UL Rated 2-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The kitchen unit is fitted with a "one touch" pressure check device to ensure reliable performance. It is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features

- Pressure check device to determine fire extinguisher's readiness status
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety clip
- Rust and impact resistant nylon handle
- 1.5 lb of fire extinguishing agent (Average)
- 2 year limited warranty
- UL approved bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-40130-7

ARLIMITE 2





At a Glance

- Model Kitchen KK2
- Regular Dry Chemical
- UL listed
- UL rated 2-B:C
- Sodium Bicarbonate
- 2 year limited warranty
- Suitable for use on liquid & energized electrical fires

Product Specification

For use on the following

types of fire:

r roduct Specification	
Net agent weight (Average)	1.5 lb
Unit weight (Average)	2 lb
Diameter	2.9 inches
Height	10 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon

Packaging Options



Also available in P.O.P 9 pcs tray pack. Part number 44013016.

